



Specifications LED Downlight 18W  
1620lm 120D - 840 Cool White |  
Cutout 175mm - Replaces 2x18W

[View Product](#)

General Information

|                          |                                   |
|--------------------------|-----------------------------------|
| SKU                      | 245415                            |
| EAN                      | 8719157042925                     |
| Brand                    | Non-branded                       |
| Manufacturer Name        | White label - Downlight 18W 4000K |
| Any Lamp all-in warranty | 2 Years                           |
| Average Lifetime (h)     | 50000                             |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x18              |
| Wattage                     | 18                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |

|                          |                          |
|--------------------------|--------------------------|
| Beam Angle (degree)      | 120                      |
| Luminous Flux (Lumen)    | 1620                     |
| Luminous Efficacy (lm/W) | 90                       |
| Power factor             | >0.90                    |
| Installation Depth (mm)  | 80                       |
| Unified Glare Rating     | < 22 - for general areas |
| Product Type Category    | LED Downlight            |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 175               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +40        |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Fixture Connection     | Cable             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 200 |
| Diameter (mm) | 190 |

## Sensor Information

## Why Any-lamp?

|                                                                                                                                                                                                                                                                   |           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Type of sensor                                                                                                                                                                                                                                                    | No Sensor |
|  Order from the <b>largest lighting specialist</b> in Europe  <b>Customised</b> quotation |           |
|  Up to <b>7 years warranty</b>  <b>Easy</b> return process                                  |           |