



**Specifications Philips LED Panel  
FlexBlend RC340B White 25.5W  
3600lm - 940 Cool White | 60x60cm -  
UGR <19 - Best Colour Rendering -  
Motion and Light Sensor**

[View Product](#)

## General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 243179                                  |
| EAN                      | 8719514708303                           |
| Brand                    | Philips                                 |
| Manufacturer Name        | RC340B LED36S/940 SRD W60L60 VPC PCS U4 |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 50000                                   |
| Series                   | RC340B                                  |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 25.5               |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 940 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 90-99              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 3600               |

|                          |                               |
|--------------------------|-------------------------------|
| Luminous Efficacy (lm/W) | 141                           |
| IP-rating                | IP54                          |
| Impact Protection (IK)   | IK02 - 0.20 joule             |
| Fixture Connection       | PI [Push-in connector 3-pole] |
| Power factor             | >0.90                         |
| Product Type Category    | LED Panel                     |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| EOC8                  | 70830300                       |
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Operating Temperature | +10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 597     |
| Width (mm)     | 597     |
| Height (mm)    | 60      |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

Light Sensor



**Easy** return process